




Potência (Power)	Tensão (Voltage)
15,5W	85~320Vca/108~250Vcc
28W	

Temperatura de cor CCT- Correlated Color Temperature	
CW	6500K
NW	4000K
NW	5000K
WW	3300K

Marcação/Marking	
Grau de Proteção (IP) (Protection Degree)	IP44
	IP44W

Sobressalentes/Spare	
Código(Cod)	Item(Item)
ML927002SAF	Difusor Leitoso
MI9270009	Difusor Transparente
Ver catálogo	Driver

Curva fotométrica(Photometric Curve)



Descrição do Produto/Product description

Luminária metálica à prova de tempo com LED Maccomevap, com opção de interruptor e/ou tomada.

Corpo: Aço carbono ou aço inox;
Cor: Pintura a pó eletrostática (Preta ou Branca; Outras sob consulta)
Difusor: Policarbonato (leitoso ou transparente);
Refletora: Branco;
Interruptor: Bipolar;
Tomada: Universal;
Transformador Isolador: 90~240;
Driver: Incluso;
Entrada: Por ilhós de neoprene;
Terminais: Para cabos de até 4mm²;
Normas Técnicas: ABNT NBR IEC 60529.

Metal time-proof luminaire with LED Maccomevap, with switch and/or socket option.

Body: Carbon steel or stainless steel;
Color: Electrostatic powder paint (Black or White; Others upon request)
Diffuser: Polycarbonate (milky or transparent);
Reflector: White;
Switch: Bipolar;
Socket: Universal;
Isolator Transformer: 90~240;
Driver: Included;
Entrance: By neoprene islands;
Terminals: For cables up to 4mm²;
Technical standards: ABNT NBR IEC 60529.

