



Descrição do Produto/Product description

Luminária metálica à prova de tempo, para uma lâmpada tubo LED, com opção de interruptor e/ou tomada.

Corpo: Aço carbono ou aço inox;

Cor: Pintura a pó eletrostática (Preta ou Branca; Outras sob consulta);

Difusor: Policarbonato (leitoso ou transparente);

Refletora: Branco;

Lâmpada: Tubo LED;

Porta Lâmpada: Antivibratório Bi-pino;

Interruptor: Bipolar;

Tomada: Universal;

Transformador Isolador: 90~240V;

Reator: Incluso;

Entrada: Por ilhós de neoprene;


Terminais: Para cabos de até 4mm²;

Normas Técnicas: ABNT NBR IEC 60529.

Potência (Power)	Tensão (Voltage)
1x8/10W	100~240Vca
1x18W	

Temperatura de cor CCT- Correlated Color Temperature	
CW	6500K
NW	4000K
NW	5000K
WW	3300K

Marcação/Marking	
Grau de Proteção (IP) (Protection Degree)	IP44
	IP44W
Sobressalentes/Spare	
Código(Code)	Item(Item)
ML927002SAF	Difusor Leitoso/Milky diffuser
MI9270009	Difusor Transparente/transparent diffuser
Ver catálogo	Reator/Reactor



Metal time-proof luminaire, for a LED tube lamp, with switch and/or socket option.

Body: Carbon steel or stainless steel;

Color: Electrostatic powder paint (Black or White; Others upon request);

Diffuser: Polycarbonate (milky or transparent);

Reflector: White;

Lamp: LED tube;

Lamp port: Anti-vibration Bi-pino;

Switch: Bipolar;

Socket: Universal;

Isolator Transformer: 90~240V;

Reactor: Included;

Entrance: By neoprene islands;

Terminals: For cables up to 4mm²;

Technical standards: ABNT NBR IEC 60529.

