




Potência (Power)	Tensão (Voltage)
1x8W	127V ou 220V
1x15W	
1x20W	
1x40W	

Marcação/Marking	
Grau de Proteção (IP) (Protection Degree)	IP44
	IP44W

Sobressalentes/Spare	
Código(Code)	Item(Item)
ML927002SAF	Difusor Leitoso
MI9270009	Difusor Transparente
Ver catálogo	Reator



Descrição do Produto/Product description

Luminária metálica à prova de tempo, para uma lâmpada fluorescente, com opção de interruptor e/ou tomada.

Corpo: Aço carbono ou aço inox;

Cor: Pintura a pó eletrostática (Preta ou Branca; Outras sob consulta)

Difusor: Policarbonato (leitoso ou transparente);

Refletora: Branco;

Lâmpada: Fluorescente tubular (FL);

Porta Lâmpada: Antivibratório Bi-pino;

Interruptor: Bipolar;

Tomada: Universal;

Transformador Isolador: 127V ou 220V;

Reator: Incluso;

Entrada: Por ilhós de neoprene;

Terminais: Para cabos de até 4mm²;

Normas Técnicas: ABNT NBR IEC 60529.

Metal time-proof luminaire, for a fluorescent lamp, with switch and/or socket option.

Body: Carbon steel or stainless steel;

Color: Electrostatic powder paint (Black or White; Others upon request)

Diffuser: Polycarbonate (milky or transparent);

Reflector: White;

Lamp: Tubular fluorescent (FL);

Lamp port: Anti-vibration Bi-pino;

Switch: Bipolar;

Socket: Universal;

Isolator Transformer: 127V or 220V;

Reactor: Included;

Entrance: By neoprene islands;

Terminals: For cables up to 4mm².

Technical standards: ABNT NBR IEC 60529.

