



Potência (Power)	Tensão (Voltage)	Fluxo Luminoso (Luminous flux)
250W	90~305Vca	30.102 Lm
300W		36.300 Lm
350W		42.700 Lm
400W		48.400 Lm

*Fluxo luminoso referente à CW./Luminous flux referring to CW.

*Fluxo luminoso NW e WW solicitar./Luminous flux NW and WW request.

Marcação/Marking	
Grau de Proteção (IP) (Protection degree)	IP66
Vida útil (Service life)	> 50.000h
Led(Led)	CREE

Aplicação/ Application

Desenvolvida para uso em áreas industriais, iluminação pública, quadras poliesportivas, praças de pedágio, estacionamentos, condomínios, pátios, galpões industriais, terminais marítimos, terminais aeroportuários, shoppings centers entre outras aplicações que requerem grande fluxo de luminosidade. Desenvolvida para uso em áreas industriais, iluminação pública, quadras poliesportivas, praças de pedágio, estacionamentos, condomínios, pátios, galpões industriais, terminais marítimos, terminais aeroportuários, shoppings centers entre outras aplicações que requerem grande fluxo de luminosidade.

Developed for use in industrial areas, street lighting, sports courts, toll plazas, parking lots, condos, courtyards, industrial sheds, maritime terminals, airport terminals, shopping malls centers among other applications that require high brightness flow. Developed for use in industrial areas, street lighting, sports courts, toll plazas, parking lots, condos, patios, industrial sheds, maritime terminals, airport terminals, shopping malls centers among other applications that require high brightness flow.

Descrição do Produto/Product Description

Luminária LED / Projetor LED estanque, com compartimento do driver incorporado.

Corpo: Alumínio injetado;

Acabamento: Pintura a pó eletrostática (Cinza; Outras sob consulta)

Difusor: Policarbonato transparente, policarbonato opaco ou vidro temperado;

Entrada: Por prensa cabo;

Fator de potência: >0,95;

Peso: 25Kg;

Nota: Outras tensões sob consulta.

LED lamp / waterproof LED projector, with built-in driver compartment.

Body: Injected aluminum;

Finish: Electrostatic powder painting (gray; others on request)

Diffuser: Transparent polycarbonate, opaque polycarbonate or tempered glass;

Input: By cable press;

Power factor: >0.95;

Weight: 25kg;

Note: Other voltages on request.

DESENHO DIMENSIONAL / DIMENSION DRAWING (mm)

